



Medidas en milímetros

ØD1xØD2	Cód.	A	B	PN
16 x 1/2"	TEC1601612I	115	53	16
16 x 3/4"	TEC1601634I	115	56	16
20 x 1/2"	TEC1602012I	144	57	16
20 x 3/4"	TEC1602034I	145	59	16
25 x 1/2"	TEC1602512I	148	63	16
25 x 3/4"	TEC1602534I	150	66	16
25 x 1"	TEC160251I	149	66	16
32 x 1/2"	TEC1603212I	185	73	16
32 x 3/4"	TEC1603234I	185	73	16
32 x 1"	TEC160321I	185	73	16
32 x 1 1/4"	TEC16032114I	182	82	16
40 x 1"	TEC160401I	225	91	16
40 x 1 1/4"	TEC16040114I	225	89	16
40 x 1 1/2"	TEC16040112I	225	105	16
50 x 1 1/4"	TEC16050114I	254	105	16
50 x 1 1/2"	TEC16050112I	254	104	16
50 x 2"	TEC160502I	254	105	16
63 x 1 1/2"	TEC16063112I	295	119	16
63 x 2"	TEC160632I	295	119	16
63 x 2 1/2"	TEC10063212I	295	119	10
75 x 2"	TEC100752I	344	141	10
75 x 2 1/2"	TEC10075212I	344	141	10
75 x 3"	TEC100753I	344	141	10
90 x 2 1/2"	TEC10090212I	430	182	10
90 x 3"	TEC100903I	430	182	10
110 x 3"	TEC101103I	495	212	10
110 x 4"	TEC101104I	495	212	10

Fittings de polipropileno (PP)

Mayor resistencia mecánica y a agentes externos (sol, golpes, etc.)

Garra de Poliacetal o CPVC

O'Ring de EPDM o VITON

Certificaciones: UNI 9561 - DIN 8076 - ISO 17885 - EN 10226-1 (ISO 7/1)