



Medidas en milímetros

$\varnothing D1 \times \varnothing D2$	Cód.	A	B	PN
16 x 1/2"	TEC1601612E	117	56	16
16 x 3/4"	TEC1601634E	117	56	16
20 x 1/2"	TEC1602012E	144	58	16
20 x 3/4"	TEC1602034E	144	58	16
25 x 1/2"	TEC1602512E	149	64	16
25 x 3/4"	TEC1602534E	149	64	16
25 x 1"	TEC160251E	149	64	16
32 x 1/2"	TEC1603212E	185	73	16
32 x 3/4"	TEC1603234E	185	73	16
32 x 1"	TEC160321E	185	73	16
32 x 1 1/4"	TEC16032114E	185	73	16
40 x 1"	TEC160401E	225	91	16
40 x 1 1/4"	TEC16040114E	225	91	16
40 x 1 1/2"	TEC16040112E	225	91	16
50 x 1 1/4"	TEC16050114E	250	106	16
50 x 1 1/2"	TEC16050112E	250	106	16
50 x 2"	TEC160502E	250	106	16
63 x 1 1/2"	TEC16063112E	292	123	16
63 x 2"	TEC160632E	292	123	16
63 x 2 1/2"	TEC16063212E	292	123	16
75 x 2 1/2"	TEC10075212E	343	145	10
75 x 3"	TEC100753E	343	145	10
90 x 3"	TEC100903E	425	180	10
110 x 4"	TEC101104E	493	214	10

Fittings de polipropileno (PP)

Mayor resistencia mecánica y a agentes externos (sol, golpes, etc.)

Garra de Poliacetal o CPVC

O'Ring de EPDM o VITON

Certificaciones: UNI 9561 - DIN 8076 - ISO 17885 - EN 10226-1 (ISO 7/1)

