



Medidas en milímetros

øD1xøD2	Cód.	A	B	PN
16 x 1/2"	TC1601612I	68	39	16
16 x 3/4"	TC1601634I	68	39	16
20 x 1/2"	TC1602012I	74	47	16
20 x 3/4"	TC1602034I	80	47	16
25 x 1/2"	TC1602512I	74	53	16
25 x 3/4"	TC1602534I	82	53	16
25 x 1"	TC160251I	83	53	16
32 x 1/2"	TC1603212I	88	64	16
32 x 3/4"	TC1603234I	88	64	16
32 x 1"	TC160321I	88	64	16
32 x 1 1/4"	TC16032114I	98	64	16
40 x 1"	TC160401I	98	82	16
40 x 1 1/4"	TC16040114I	101	82	16
40 x 1 1/2"	TC16040112I	110	82	16
50 x 1 1/4"	TC16050114I	124	96	16

øD1xøD2	Cód.	A	B	PN
50 x 1 1/2"	TC16050112I	124	96	16
50 x 2"	TC160502I	124	96	16
63 x 1 1/2"	TC16063112I	144	112	16
63 x 2"	TC160632I	144	112	16
63 x 2 1/2"	TC16063212I	144	112	16
75 x 2"	TC100752I	154	131	10
75 x 2 1/2"	TC10075212I	154	131	10
75 x 3"	TC100753I	154	131	10
90 x 2"	TC100902I	205	151	10
90 x 2 1/2"	TC10090212I	205	151	10
90 x 3"	TC100903I	205	151	10
90 x 4"	TC100904I	205	151	10
110 x 2"	TC101102I	238	181	10
110 x 3"	TC101103I	238	181	10
110 x 4"	TC101104I	238	181	10

Fittings de polipropileno (PP)

Mayor resistencia mecánica y a agentes externos (sol, golpes, etc.)

Garra de Poliacetal o CPVC

O'Ring de EPDM o VITON

Certificaciones: UNI 9561 - DIN 8076 - ISO 17885 - EN 10226-1 (ISO 7/1)